




Project Name: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____

Specifications



Material:
 Durable A356 cast aluminum and aluminum sheet metal. Hardware is stainless steel or zinc-plated steel.

Fixture Mounting:
 Post Mount: Post Cap with set screws.

Drivers:
 Universal Voltage 120-277V is standard. 0-10V dimming is standard. (Refer to Driver Specification section for other specifications.)

Dark Sky Friendly:
 To maintain dark sky friendly compatibility: ≤ 3000K

Electrical:
 A lightning surge protective device is standard (20KA³ Max/10KA² Nominal). Approximately 12" of pull wire extends from luminaire. All luminaires are prewired with 0-10V dimming leads. Post Arms and Wall Mounts are also prewired with line voltage & dimming leads.

Finish:
 A polyester powder coat high quality finish. Marine grade finish is available.

Certifications:
 UL Listed for outdoor, wet location. LED is IP66.

Modifications:
 Consult factory for custom or modified designs.

Buy American:
 This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)

LA211 LED

EPA: 0.63
 Weight: 25 lbs.

Catalog Logic						
LA211	1	CPS46W18	T5	40K	PC	PA5651 - 72
Luminaire Series	Fixture Orientation	Light Source & Wattage	Optics	CCT	Accessories	Mounting Source Finish

Catalog Number								
1	2	3	4	5	6	7	8	
LA211	1							

1	FIXTURE ORIENTATION
1	(Post)

2	LIGHT SOURCE & WATTAGES
TIR Performance Platform	
CPS30W18	(30W TIR Performance Platform)
CPS39W18	(39W TIR Performance Platform, CA Title 24)
CPS46W18	(46W TIR Performance Platform)
Edge-Lit LED Small*	
E030LDS	(30W Small Edge-Lit LED Comfort Solution)
E039LDS	(39W Small Edge-Lit LED Comfort Solution, CA Title 24)
E050LDS	(50W Small Edge-Lit LED Comfort Solution)
*See LED Performance Charts for distribution type compatibility.	

3	OPTICS
T2	(Type II)
T3	(Type III)
T4	(Type IV)
T5	(Type V)

4	CCT (COLOR TEMPERATURE)
27K	(2700K)
30K	(3000K)
35K	(3500K)
40K	(4000K)
*Consult Factory for 5000K	

5	ACCESSORIES
HSS90	(90° House Side Shield)
HSS120	(120° House Side Shield)
*EMG-LED10	(10W LED Emergency Driver, See Below For Compatibility)
*EMG-LED20	(20W LED Emergency Driver, See Below For Compatibility)
HLMSPC-06	(On/Off Motion Sensor/Photocell, High/Low field-configurable; 15' - 30' Sensor Mounting Height)
HLMSPC-10	(On/Off Motion Sensor/Photocell, High/Low field-configurable; 8' - 15' Sensor Mounting Height)
PC	(Button Photo Cell)
TLPC	(ANSI C136.41 Twist Lock Photocell, includes receptacle and 120-277V photo cell)
TL5	(ANSI C136.41 5-Pin Twist Lock Receptacle only)
TL7	(ANSI C136.41 7-Pin Twist Lock Receptacle only)
AD	(AstroDIM™ - Night-time dimming, consult factory)
FAID	(Field Adjustable Internal Dimmer)
*Most Emergency Drivers are remote mount only (consult factory). 10W & 30W Emergency Drivers are not compatible with all LED Light Source and Wattages. For percent lumens in emergency mode, see Technical Section	

6	MOUNTING SOURCE
Post Mount Options	
S3 (Slips over Ø3" pole or tenon)	PA3111
S4 (Slips over Ø4" pole or tenon)	PA3113
S5 (Slips over Ø5" pole or tenon)	PA5151
TN3 (Mounts to Ø3" pole with Ø2-3/8" x 4" tenon)	PA5153
TN4 (Mounts to Ø4" pole with Ø2-3/8" x 4" tenon)	PA5411
TN5 (Mounts to Ø5" pole with Ø2-3/8" x 4" tenon)	PA5413
OM (Other Mounting, Please Specify)	PA8521
All Poles All Post Mounts All Wall Mounts	
Column Mount	
CM Column Mount	
See last page for popular mounting sizes/styles.	

7	FINISHES					
*Premium and Marine Grade Finish have additional charges						
Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade*	Marine Grade*
Aspen Green	10	10M	Copper Clay	53	53M	
Cantaloupe	11	11M	Silver	56	56M	
Lilac	12	12M	Black Verde	61	61M	
Putty	13	13M	Painted Chrome	70	70M	
Raw Unfinished	40	NA	Painted Copper	71	71M	
Black	41	41M	Textured Black	72	72M	
Forest Green	42	42M	Matte Black	73	73M	
Bright Red	43	43M	Textured Architectural Bronze	76	76M	
White	44	44M	Textured White	77	77M	
Bright Blue	45	45M	Textured Silver	78	78M	
Sunny Yellow	46	46M	PREMIUM FINISH	Premium Grade*	Marine Grade*	
Aqua Green	47	47M	Textured Desert	80	80M	
Galvanized	49	NA	Graystone	82	82M	
Navy	50	50M	Oil Rubbed Bronze	83	83M	
Architectural Bronze	51	51M	Carbon Graphite	96	96M	
Patina Verde	52	52M				
Consult Factory for additional paint charges and availability.						

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

PERFORMANCE TABLE - TIR PLATFORM - DELIVERED LUMENS

LED CATALOG	WATTS	DISTRIBUTION	2700K				3000K				3500K				4000K							
			DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G
CPS30W18	30W	TYPE II	3025	101	1	0	1	3262	109	1	0	1	3284	109	1	0	1	3284	109	1	0	1
		TYPE III	2993	100	1	0	1	3229	108	1	0	1	3250	108	1	0	1	3250	108	1	0	1
		TYPE IV	3204	107	1	0	1	3456	115	1	0	1	3478	116	1	0	1	3478	116	1	0	1
		TYPE V	3245	108	2	0	1	3500	117	2	0	1	3524	117	2	0	1	3524	117	2	0	1
CPS39W18	39W	TYPE II	3932	101	1	0	1	4241	109	1	0	1	4269	109	1	0	1	4269	109	1	0	1
		TYPE III	3891	100	1	0	1	4197	108	1	0	1	4225	108	1	0	1	4225	108	1	0	1
		TYPE IV	4165	107	1	0	1	4492	115	1	0	1	4522	116	1	0	1	4522	116	1	0	1
		TYPE V	4219	108	3	0	1	4551	117	3	0	1	4581	117	3	0	1	4581	117	3	0	1
CPS46W18	46W	TYPE II	4638	101	1	0	1	5002	109	1	0	1	5035	109	1	0	1	5035	109	1	0	1
		TYPE III	4590	100	1	0	1	4950	108	1	0	1	4983	108	1	0	1	4983	108	1	0	1
		TYPE IV	4913	107	1	0	1	5299	115	1	0	1	5334	116	1	0	1	5334	116	1	0	1
		TYPE V	4976	108	3	0	1	5367	117	3	0	1	5403	117	3	0	1	5403	117	3	0	1

PERFORMANCE TABLE - EDGE-LIT SMALL - DELIVERED LUMENS

LED CATALOG	WATTS	DISTRIBUTION	2700K				3000K				3500K				4000K							
			DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G
E030LDS	30W	TYPE II	2808	94	1	0	1	2901	97	1	0	1	2947	98	1	0	1	3040	101	1	0	1
		TYPE III	3053	102	1	0	1	3154	105	1	0	1	3204	107	1	0	1	3305	110	1	0	1
		TYPE IV	3124	104	1	0	1	3228	108	1	0	1	3279	109	1	0	1	3383	113	1	0	1
		TYPE V	2746	92	2	0	1	2837	95	2	0	1	2882	96	2	0	1	2973	99	2	0	1
E039LDS	39W	TYPE II	3650	94	1	0	1	3771	97	1	0	1	3831	98	1	0	1	3952	101	1	0	1
		TYPE III	3969	102	2	0	2	4100	105	2	0	2	4166	107	2	0	2	4297	110	2	0	2
		TYPE IV	4062	104	1	0	1	4196	108	1	0	1	4263	109	1	0	1	4397	113	1	0	1
		TYPE V	3570	92	1	0	1	3688	95	2	0	1	3747	96	2	0	1	3865	99	2	0	1
E050LDS	50W	TYPE II	4680	94	2	0	2	4834	97	2	0	2	4912	98	2	0	2	5066	101	2	0	2
		TYPE III	5088	102	2	0	2	5256	105	2	0	2	5340	107	2	0	2	5509	110	2	0	2
		TYPE IV	5207	104	2	0	2	5379	108	2	0	2	5465	109	2	0	2	5638	113	2	0	2
		TYPE V	4576	92	2	0	1	4728	95	2	0	1	4803	96	2	0	1	4955	99	2	0	1

EDGE-LIT LED SPECIFICATION

- Edge-Lit comfort solution
- Distributions: Type II, III, IV, V
- CCT: 2700K, 3000K, 3500K, 4000K
- Life: L70 >80,000 hours
- Ingress Protection: IP66
- Certification: UL, RoHS
- CRI: >80, 3 SDCM

DRIVER SPECIFICATION

- Universal Input 120-277V
- 0-10V Dimming to 10%
- Power Factor @ Full Load >95%
- THD @ Full Load <10%
- Constant Current Output 50/60Hz
- Operating Temperature: -40°C Minimum
- Ingress Protection: IP66
- Certifications: UL Recognized, CSA, RoHS

FINISHES

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. 5-year warranty for aluminum products. 2-year warranty for steel products.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray and is available in either a textured or gloss surface. 5-year warranty for aluminum products. 2-year warranty for steel products.

WARRANTY

See www.ANPlighting.com for complete fixture warranty.

LED warranty information

- 5 year limited warranty*
- *Limited Warranty: A typical year is defined as 4,380 hours of operation.

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

ACCESSORIES



HSS90 & HSS120



EMG-LED10, 20



HLMSPC-06 & HLMSPC-10



PC



TLPC



TL5 & TL7



FAID

POPULAR POST MOUNTS

See Post Arm Section on Website for Specification Sheets and additional post arms. Dimensions are Projection x Height.
[Click here for all Post Mount styles](#)



PA3321 / 18" x 14 3/4"



PA5151 / 14 1/4" x 19 3/4"



PA5411 / 17 7/8" x 25 1/8"



PA5611 / 18 5/8" x 26 1/2"



PA5621 / 19" x 26 1/4"



PA5651 / 20" x 26 1/4"



PA6211 / 22 3/4" x 26 1/2"



PA6311 / 17" x 23 1/4"



PA7911 / 20" x 20 5/8"



PA8031 / 20 1/2" x 20 1/4"



PA8521 / 18 1/4" x 14 1/2"



PA8571 / 24" x 47"

POPULAR WALL MOUNTS

See Wall Mount Section on Website for Specification Sheets and additional wall mount arms. Dimensions are Projections x Height.
[Click here for all Wall Mount styles](#)



WM2141 / 18" x 12 3/16"




WM2211 / 15 1/2" x 15 7/8"



WM3001 / 11" x 8 7/8"



WM3351 / 14 1/2" x 17"



WM4511 / 17" x 8"



WM5131 / 11" x 16 3/8"



WM5161 / 15 3/4" x 17 3/4"



WM5311 / 10 7/8" x 10"



WM5601 / 17 7/8" x 14"



WM5611 / 17 5/8" x 22"



WM7421 / 16 3/8" x 15 3/4"



WM8021 / 19 1/4" x 16 3/8"

COLUMN MOUNT



CM / 5 3/4" SQ x 3 1/2" H

Project Name: _____

Fixture Type: _____ Quantity: _____

Customer: _____

FINISHES COLORS

STANDARD																				PREMIUM								
WHITE	TEXTURED WHITE	SILVER	PAINTED CHROME	PAINTED GALVANIZED	PUTTY	TEXTURED SILVER	TEXTURED BLACK	MATTE BLACK	BLACK	BLACK VERDE	PATINA VERDE	FOREST GREEN	AQUA GREEN	ASPEN GREEN	BRIGHT BLUE	NAVY	SUNNY YELLOW	CANTALOUPE	LILAC	BRIGHT RED	PAINTED COPPER	COPPER CLAY	ARCHITECTURAL BRONZE	TEXTURED ARCHITECTURAL BRONZE	TEXTURED DESERT	GRAYSTONE	OIL RUBBED BRONZE	CARBON GRAPHITE